

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Previously Presented) A method for dynamically segmenting a digital data file resident within at least one digital data storage device of multiple digital data storage devices associated with a first computing system to facilitate transfer of the segmented digital data file from said first computing system to at least one of a plurality of second computing systems, whereby said method comprises the steps of
  - a) requesting an identifier for said digital data file;
  - b) requesting a range of locations within the multiple data storage devices where said digital data file is resident;
  - c) calculating a new segment size list for said digital data file describing a fragmentation of said digital data file as a function of demand for all digital data files resident on said digital data storage devices, size of each digital data file of all digital data files, amount of retention space available on each of the plurality of digital data storage devices, and available bandwidth for communication with the plurality of second computing systems;

- 17           d) if said digital data file has been previously segmented, comparing the new  
18           segment size list to an existing segment size list;
- 19           e) if the existing segment size list provides a more facilitated transfer of said  
20           digital data file, transferring said digital data file to the second computing  
21           system according to said existing segment size list;
- 22           f) if the new segment size list provides a more facilitated transfer of said  
23           digital file,
- 24           creating a new file identifier for each new segment ascertained by the  
25           creating of the new segment size list,
- 26           creating a new range of locations for each new segment of the digital  
27           data file to identify the location for each new segment, and
- 28           storing the digital data file at said locations for each new segment;
- 29           g) transferring each new segment of said digital data file to at least one of  
30           the second computing systems; and
- 31           repeating steps a) through g) at each request for each digital data file.

- 1    2.    (Original) The method of claim 1 wherein calculating the new segment size  
2           list comprises the steps of:
- 3           determining a number of storage devices attached to said first computing  
4           system available to retain a plurality of segments of said digital data file;

5 determining a maximum digital data transfer load for the storage devices  
6 attached to said first computing system;  
7 assigning a minimum segment size which is the smallest amount of digital  
8 data to be contained within one segment of the digital data file;  
9 calculating a first segment size as a first function of a number of the storage  
10 devices, the current digital data transfer load, the maximum digital data  
11 transfer load, and the minimum segment size;  
12 assigning a last segment size as the minimum segment size;  
13 calculating all remaining segment sizes as a second function of the number of  
14 the storage devices, the current digital data transfer load, the maximum  
15 digital data transfer load, and the minimum segment size; and  
16 partitioning said digital data file into segments whereby the first segment of  
17 the digital data file is of the first segment size, the last segment of the  
18 digital data file is of the last segment size, and all the remaining segments  
19 of the digital data file is of the remaining segment sized.

1     3.     (Original) The method of claim 2 wherein the first function to determine the  
2     first segment size is:

$$3 \quad \mathbf{Seg1} = \min(\mathbf{SegSize}_{\min}, \mathbf{V}/\mathbf{f})$$

4 where

5                    **Seg1** is the first segment size,

6                    **min** is the minimum function of two variables,

7                    **V** is a total size of the digital data file, and

8                    **f** is determined by the formula:

9                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

10                   where

11                    **N<sub>d</sub>** is the number of storage devices  
12                    available to retain the segments of  
13                    the digital data file,

14                    **M<sub>i</sub>** is the maximum digital data transfer  
15                    load, and

16                    **C<sub>i</sub>** is the current digital data transfer load.

1        4.        (Original) The method of claim 2 wherein the second function to determine  
2                   the remaining segment sizes is:

3                    
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4                    where

5                    **Segn** is the a segment size for one segment of the  
6                    remaining segments,

7                    **max** is the maximum function of two variables,

8                    **V** is a total size of the digital data file, and

9                    **f** is determined by the formula:

10                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

11                    where

12                    **N<sub>d</sub>** is the number of storage devices  
13                    available to retain the segments of  
14                    the digital data file,

15                    **M<sub>i</sub>** is the maximum digital data transfer  
16                    load, and

17                    **C<sub>i</sub>** is the current digital data transfer load.

- 1     5.     (Original) The method of claim 2 further comprising the step of:  
2           determining a file interactivity factor describing a number of jumps by the  
3           second computing system within the digital data file.

1 6. (Original) The method of claim 5 wherein the first function is further  
2 dependent upon the file interactivity factor.

1 7. (Original) The method of claim 6 wherein the first function to determine the  
2 first segment size is:

$$3 \quad \mathbf{Seg1} = \min(\mathbf{SegSize}_{\min}, V/f)$$

4 where

5                    **Seg1** is the first segment size,

6 **min** is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

$$9 \quad \mathbf{f} = \mathbf{N}_d + \left( \frac{\mathbf{M}_l}{\mathbf{M}_l - \mathbf{C}_l} \right) + \mathbf{I}$$

10 where

11  **$N_d$**  is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,

14  $M_l$  is the maximum digital data transfer  
15 load.

16  $C_i$  is the current digital data transfer load,  
17 and  
18  $I$  is the file interactivity factor.

1 8. (Original) The method of claim 5 wherein the second function is further  
2 dependent upon the file interactivity factor.

1 9. (Original) The method of claim 8 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Segn}$  is the a segment size for one segment of the  
6 remaining segments,

7  $\max$  is the maximum function of two variables,

8  $V$  is a total size of the digital data file, and

9  $f$  is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

11 where

12  $N_d$  is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,  
15  $M_l$  is the maximum digital data transfer  
16 load,  
17  $C_l$  is the current digital data transfer load,  
18 and  
19  $I$  is the file Inter activity factor.

1 10. (Original) The method of claim 2 further comprising the step of:  
2 determining a file usage factor describing a number of requests for said digital  
3 data file for a period of time.

1 11. (Original) The method of claim 10 wherein the first function is further  
2 dependent upon the file usage factor.

1 12. (Original) The method of claim 11 wherein the first function to determine the  
2 first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Seg1}$  is the first segment size,



6                    **min** is the minimum function of two variables,

7                    **V** is a total size of the digital data file, and

8                    **f** is determined by the formula:

9                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

10                   where

11                    **N<sub>d</sub>** is the number of storage devices  
12                    available to retain the segments of  
13                    the digital data file,

14                    **M<sub>i</sub>** is the maximum digital data transfer  
15                    load,

16                    **C<sub>i</sub>** is the current digital data transfer load,  
17                    and

18                    **H** is the file usage factor.

1    13.    (Original) The method of claim 9 wherein the second function is further  
2           dependent upon the file usage factor.

1    14.    (Original) The method of claim 13 wherein the second function to determine  
2           the remaining segment sizes is:

$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

where

**Segn** is the a segment size for one segment of the  
remaining segments,

**max** is the maximum function of two variables,

**V** is a total size of the digital data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

where

**N<sub>d</sub>** is the number of storage devices  
available to retain the segments of  
the digital data file,

**M<sub>i</sub>** is the maximum digital data transfer  
load,

**C<sub>i</sub>** is the current digital data transfer load,  
and

**H** is the file usage factor.

1     15.     (Original) The method of claim 2 further comprising the steps of:

2             determining a file usage factor describing a number of requests for said digital

3             data file for a period of time; and

4             determining a file interactivity factor describing a number of jumps by the

5             second computing system within the digital data file.

1     16.     (Original) The method of claim 15 wherein the first function is further  
2     dependent upon the file usage factor and the file interactivity factor.

1     17.     (Original) The method of claim 16 wherein the first function to determine the  
2     first segment size is:

$$3 \quad \mathbf{Seg1} = \min(\mathbf{SegSize}_{\min}, \mathbf{V}/\mathbf{f})$$

4 where

5                    **Seg1** is the first segment size,

6 **min** is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

$$9 \quad \mathbf{f} = \mathbf{N}_d + \left( \frac{\mathbf{M}_i}{\mathbf{M}_i - \mathbf{C}_i} \right) + \mathbf{H} + \mathbf{I}$$

10 where

11  **$N_d$**  is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,

14  $M_l$  is the maximum digital data transfer  
15 load,

16 **C<sub>l</sub>** is the current digital data transfer load,

17 **H** is the file usage factor, and

18 **I** is the file Inter activity factor.

1 18. (Original) The method of claim 15 wherein the second function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 19. (Original) The method of claim 18 wherein the second function to determine  
2 the remaining segment sizes is:

$$3 \quad \text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5                                   **Segn** is the a segment size for one segment of the  
6                                   remaining segments,

7 **max** is the maximum function of two variables,

8 **V** is a total size of the digital data file, and

9 **f** is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

11 where

12 **N<sub>d</sub>** is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15 **M<sub>i</sub>** is the maximum digital data transfer  
16 load,

17 **C<sub>i</sub>** is the current digital data transfer load,

18 **H** is the file usage factor, and

19 **I** is the file Inter activity factor.

1 20. (Original) The method of claim 1 wherein the locations at which the segments  
2 of said data file are located are within the multiple storage devices of the first  
3 computing system.

1 21. (Original) The method of claim 1 wherein the locations at which the segments  
2 of said data file are located are within multiple storage devices of the plurality  
3 of the second computing systems.

1 22. (Original) The method of claim 1 wherein the digital data file is a video file to  
2 be transferred isochronously to at least one of the second computing  
3 systems.

1 23. (Currently Amended) A digital data service system in communication with a  
2 plurality of computing systems to provide at least one digital data file of a  
3 plurality of digital data files to at least one of the plurality of computing  
4 systems, comprising:

5 a plurality of digital data file storage devices in communication with each  
6 other and with any of the plurality of computing systems for storing a  
7 plurality of dynamically generated segments of said provided data file,  
8 said segments stored within said plurality of digital data file storage  
9 devices to facilitate transfer of said provided data file to at least one of the  
10 plurality of computing systems; and

11 a segmentation apparatus in communication with the plurality of digital data  
12 file storage devices, which, at a request of any of the digital data files,  
13 dynamically fragments any requested digital data file into a plurality of  
14 segments to facilitate transfer to and processing by at least one of the  
15 computing systems of said segments, ~~wherein if said requested digital~~  
16 ~~data file has been previously segmented, a new segment size list is~~  
17 ~~compared to an existing segment size list.~~ wherein the segmentation  
18 apparatus performs the steps of:

19 a) requesting an identifier for said digital data file;

- b) requesting a range of locations within the multiple data storage devices where said digital data file is resident;
- c) calculating the new segment size list for said digital data file describing a fragmentation of said digital data file as a function of demand for all digital data files resident on said digital data storage devices, size of each digital data file of all digital data files, amount of retention space available on each of the plurality of digital data storage devices, and available bandwidth for communication with the plurality of computing systems;
- d) if said digital data file has been previously segmented, comparing the new segment size list to an existing segment size list;
- e) if the existing segment size list provides a more facilitated transfer of said digital data file, transferring said digital data file to the computing system according to said existing segment size list;
- f) if the new segment size list provides a more facilitated transfer of said digital file,
- creating a new file identifier for each new segment ascertained by the creating of the new segment size list,
- creating a new range of locations for each new segment of the digital data file to identify the location for each new segment, and

41                    storing the digital data file at said locations for each new  
42                    segment;  
43                    g) transferring each new segment of said digital data file to at least  
44                    one of the computing systems; and  
45                    h) repeating steps a) through g) at each request for each digital data  
46                    file.

1    24.    (Cancelled)

1    25.    (Currently Amended) The system of ~~claim 24~~ claim 23 wherein calculating the  
2       new segment size list comprises the steps of:

3       determining a number of storage devices attached to said first computing  
4       system available to retain a plurality of segments of said digital data file;

5       determining a maximum digital data transfer load for the storage devices  
6       attached to said first computing system;

7       assigning a minimum segment size which is the smallest amount of digital  
8       data to be contained within one segment of the digital data file;

9       calculating a first segment size as a first function of a number of the storage  
10       devices, the current digital data transfer load, the maximum digital data  
11       transfer load, and the minimum segment size;

12       assigning a last segment size as the minimum segment size;



calculating all remaining segment sizes as a second function of the number of the storage devices, the current digital data transfer load, the maximum digital data transfer load, and the minimum segment size; and partitioning said digital data file into segments whereby the first segment of the digital data file is of the first segment size, the last segment of the digital data file is of the last segment size, and all the remaining segments of the digital data file is of the remaining segment sized.

1     26.     (Original) The system of claim 25 wherein the segmentation apparatus the  
2     further performs the steps of:

3 assigning one of the number of storage devices to retain each segment of the  
4 digital data file; and

5        assigning an address within the storage devices to identify the location of an  
6        assigned segment.

1     27.     (Original) The system of claim 25 wherein the first function to determine the  
2     first segment size is:

$$3 \quad \mathbf{Seg1} = \min(\mathbf{SegSize}_{\min}, V/f)$$

4 where

5                    **Seg1** is the first segment size,

6  $\min$  is the minimum function of two variables.

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

10 where

11 **N<sub>d</sub>** is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,

14 **M<sub>i</sub>** is the maximum digital data transfer  
15 load, and

16 **C<sub>i</sub>** is the current digital data transfer load.

1 28. (Original) The system of claim 25 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Segn** is the a segment size for one segment of the  
6 remaining segments,

7 **max** is the maximum function of two variables,

8 V is a total size of the digital data file, and

9 f is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

11 where

12  $N_d$  is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15  $M_i$  is the maximum digital data transfer  
16 load, and

17  $C_i$  is the current digital data transfer load.

1 29. (Original) The system of claim 25 further comprising the step of:

2 determining a file interactivity factor describing a number of jumps by the  
3 computing system within the digital data file.

1 30. (Original) The system of claim 29 wherein the first function is further  
2 dependent upon the file interactivity factor.

1 31. (Original) The system of claim 30 wherein the first function to determine the  
2 first segment size is:

3                                    **Seg1 = min(SegSize<sub>min</sub>, V/f)**

4                                    where

5                                    **Seg1** is the first segment size,

6                                    **min** is the minimum function of two variables,

7                                    **V** is a total size of the digital data file, and

8                                    **f** is determined by the formula:

9                                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

10                                   where

11                                   **N<sub>d</sub>** is the number of storage devices  
12                                   available to retain the segments of  
13                                   the digital data file,

14                                   **M<sub>i</sub>** is the maximum digital data transfer  
15                                   load,

16                                   **C<sub>i</sub>** is the current digital data transfer load,  
17                                   and

18                                   **I** is the file interactivity factor.

1 32. (Original) The system of claim 29 wherein the second function is further  
2 dependent upon the file interactivity factor.

1 33. (Original) The system of claim 32 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Segn** is the a segment size for one segment of the  
6 remaining segments,

7 **max** is the maximum function of two variables,

8 **V** is a total size of the digital data file, and

9 **f** is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

11 where

12 **N<sub>d</sub>** is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15  $M_i$  is the maximum digital data transfer  
16 load,

17  $C_i$  is the current digital data transfer load,  
18 and

19  $I$  is the file Inter activity factor.

1 34. (Original) The system of claim 25 further comprising the step of:  
2 determining a file usage factor describing a number of requests for said digital  
3 data file for a period of time.

1 35. (Original) The system of claim 34 wherein the first function is further  
2 dependent upon the file usage factor.

1 36. (Original) The system of claim 35 wherein the first function to determine the  
2 first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Seg1}$  is the first segment size,

6  $\min$  is the minimum function of two variables,

7  $V$  is a total size of the digital data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

10 where

11 **N<sub>d</sub>** is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,

14 **M<sub>i</sub>** is the maximum digital data transfer  
15 load,

16 **C<sub>i</sub>** is the current digital data transfer load,  
17 and

18 **H** is the file usage factor.

1 37. (Original) The system of claim 34 wherein the second function is further  
2 dependent upon the file usage factor.

1 38. (Original) The system of claim 37 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5                    **Segn** is the a segment size for one segment of the  
6                    remaining segments,

7                    **max** is the maximum function of two variables,

8                    **V** is a total size of the digital data file, and

9                    **f** is determined by the formula:

10                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

11                    where

12                    **N<sub>d</sub>** is the number of storage devices  
13                    available to retain the segments of  
14                    the digital data file,

15                    **M<sub>i</sub>** is the maximum digital data transfer  
16                    load,

17                    **C<sub>i</sub>** is the current digital data transfer load,  
18                    and

19                    **H** is the file usage factor.

1    39.    (Original) The system of claim 25 further comprising the steps of:



2 determining a file usage factor describing a number of requests for said digital  
3 data file for a period of time; and  
4 determining a file interactivity factor describing a number of jumps by the  
5 computing system within the digital data file.

1 40. (Original) The system of claim 39 wherein the first function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 41. (Original) The system of claim 40 wherein the first function to determine the  
2 first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Seg1** is the first segment size,

6 **min** is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

10 where

11  $N_d$  is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,  
14  $M_l$  is the maximum digital data transfer  
15 load,  
16  $C_l$  is the current digital data transfer load,  
17  $H$  is the file usage factor, and  
18  $I$  is the file Inter activity factor.

1 42. (Original) The system of claim 39 wherein the second function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 43. (Original) The system of claim 42 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Segn}$  is the a segment size for one segment of the  
6 remaining segments,

7  $\max$  is the maximum function of two variables,

8  $V$  is a total size of the digital data file, and

9 **f** is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

11 where

12 **N<sub>d</sub>** is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15 **M<sub>i</sub>** is the maximum digital data transfer  
16 load,

17 **C<sub>i</sub>** is the current digital data transfer load,

18 **H** is the file usage factor, and

19 **I** is the file Inter activity factor.

1 44. (Original) The system of claim 25 wherein the locations at which the  
2 segments of said data file are located are within the multiple storage devices  
3 of the first computing system.

1 45. (Original) The system of claim 25 wherein the locations at which the  
2 segments of said data file are located are within multiple storage devices of  
3 the plurality of the computing systems.

1    46.    (Original) The system of claim 23 wherein the digital data file is a video file to  
2           be transferred isochronously to the computing system.

1    47.    (Previously Presented) An apparatus for dynamically segmenting a digital  
2           data file resident within at least one digital data storage device of multiple  
3           digital data storage devices associated with a first computing system to  
4           facilitate transfer of the segmented digital data file from said first computing  
5           system to at least one of a plurality of second computing systems, whereby  
6           said apparatus comprises the steps of

7           a) means for requesting an identifier for said digital data file;

8           b) means for requesting a range of locations within the multiple data storage  
9           devices where said digital data file is resident;

10          c) means for calculating a new segment size list for said digital data file  
11           describing a fragmentation of said digital data file as a function of demand  
12           for all digital data files resident on said digital data storage devices, size of  
13           each digital data file of all digital data files, amount of retention space  
14           available on each of the plurality of digital data storage devices, and  
15           available bandwidth for communication with the plurality of second  
16           computing systems;

17          e) means comparing the new segment size list to an existing segment size  
18           list, if said digital data file has been previously segmented;

19 f) means for transferring said digital data file to the second computing  
20 system according to said existing segment size list, if the existing segment  
21 size list provides a more facilitated transfer of said digital data file;

22 g) means for:

23 creating a new file identifier for each new segment ascertained by the  
24 creating of the new segment size list,

25 creating a new range of locations for each new segment of the digital  
26 data file to identify the location for each new segment, and

27 storing the digital data file at said locations for each new segment,

28 if the new segment size list provides a more facilitated transfer of said digital  
29 file;

30 h) means for transferring each new segment of said digital data file to at  
31 least one of the second computing systems; and

32 means for executing the means of steps of a) through h) at each request for  
33 each digital data file.

1 48. (Original) The apparatus of claim 47 wherein the means for calculating the  
2 new segment size list comprises:

3 means for determining a number of storage devices attached to said first  
4 computing system available to retain a plurality of segments of said digital  
5 data file;

6 means for determining a maximum digital data transfer load for the storage  
7 devices attached to said first computing system;

8 means for assigning a minimum segment size which is the smallest amount  
9 of digital data to be contained within one segment of the digital data file;

10 means for calculating a first segment size as a first function of a number of  
11 the storage devices, the current digital data transfer load, the maximum  
12 digital data transfer load, and the minimum segment size;

13 means for assigning a last segment size as the minimum segment size;

14 means for calculating all remaining segment sizes as a second function of the  
15 number of the storage devices, the current digital data transfer load, the  
16 maximum digital data transfer load, and the minimum segment size; and

17 means for partitioning said digital data file into segments whereby the first  
18 segment of the digital data file is of the first segment size, the last  
19 segment of the digital data file is of the last segment size, and all the  
20 remaining segments of the digital data file is of the remaining segment  
21 sized.

49. (Original) The apparatus of claim 48 wherein the first function to determine the first segment size is:

$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

where

**Seg1** is the first segment size,

**min** is the minimum function of two variables,

**V** is a total size of the digital data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

where

**N<sub>d</sub>** is the number of storage devices  
available to retain the segments of  
the digital data file,

**M<sub>i</sub>** is the maximum digital data transfer  
load, and

**C<sub>i</sub>** is the current digital data transfer load.

50. (Original) The apparatus of claim 48 wherein the second function to  
determine the remaining segment sizes is:

$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

where

**Segn** is the a segment size for one segment of the  
remaining segments,

**max** is the maximum function of two variables,

**V** is a total size of the digital data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

where

**N<sub>d</sub>** is the number of storage devices  
available to retain the segments of  
the digital data file,

**M<sub>i</sub>** is the maximum digital data transfer  
load, and

**C<sub>i</sub>** is the current digital data transfer load.



1 51. (Original) The apparatus of claim 48 further comprising:  
2 means for determining a file interactivity factor describing a number of jumps  
3 by the second computing system within the digital data file.

1 52. (Original) The apparatus of claim 51 wherein the first function is further  
2 dependent upon the file interactivity factor.

1 53. (Original) The apparatus of claim 52 wherein the first function to determine  
2 the first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Seg1** is the first segment size,

6 **min** is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + 1$$

10 where

11  $N_d$  is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,  
14  $M_l$  is the maximum digital data transfer  
15 load,  
16  $C_l$  is the current digital data transfer load,  
17 and  
18  $I$  is the file interactivity factor.

1 54. (Original) The apparatus of claim 51 wherein the second function is further  
2 dependent upon the file interactivity factor.

1 55. (Original) The apparatus of claim 54 wherein the second function to  
2 determine the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Segn}$  is the a segment size for one segment of the  
6 remaining segments,

7  $\max$  is the maximum function of two variables,

8  $V$  is a total size of the digital data file, and

9 f is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

11 where

12  $N_d$  is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15  $M_i$  is the maximum digital data transfer  
16 load,

17  $C_i$  is the current digital data transfer load,  
18 and

19  $I$  is the file Inter activity factor.

1 56. (Original) The apparatus of claim 48 further comprises:

2 means for determining a file usage factor describing a number of requests for  
3 said digital data file for a period of time.

1 57. (Original) The apparatus of claim 56 wherein the first function is further  
2 dependent upon the file usage factor.

1 58. (Original) The apparatus of claim 57 wherein the first function to determine  
2 the first segment size is:

3                                    **Seg1 = min(SegSize<sub>min</sub>, V/f)**

4                                    where

5                                    **Seg1** is the first segment size,

6                                    **min** is the minimum function of two variables,

7                                    **V** is a total size of the digital data file, and

8                                    **f** is determined by the formula:

9                                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

10                                   where

11                                   **N<sub>d</sub>** is the number of storage devices  
12                                   available to retain the segments of  
13                                   the digital data file,

14                                   **M<sub>i</sub>** is the maximum digital data transfer  
15                                   load,

16                                   **C<sub>i</sub>** is the current digital data transfer load,  
17                                   and

18                                   **H** is the file usage factor.

1 59. (Original) The apparatus of claim 56 wherein the second function is further  
2 dependent upon the file usage factor.

1 60. (Original) The apparatus of claim 59 wherein the second function to  
2 determine the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5 Segn is the a segment size for one segment of the  
6 remaining segments,

7 max is the maximum function of two variables,

8 V is a total size of the digital data file, and

9 f is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

11 where

12  $N_d$  is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15  $M_i$  is the maximum digital data transfer  
16 load,  
17  $C_i$  is the current digital data transfer load,  
18 and  
19  $H$  is the file usage factor.

1 61. (Original) The apparatus of claim 48 further comprises:  
2 means for determining a file usage factor describing a number of requests for  
3 said digital data file for a period of time; and  
4 means for determining a file interactivity factor describing a number of jumps  
5 by the second computing system within the digital data file.

1 62. (Original) The apparatus of claim 61 wherein the first function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 63. (Original) The apparatus of claim 62 wherein the first function to determine  
2 the first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Seg1}$  is the first segment size,

6  $\min$  is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

10 where

11 **N<sub>d</sub>** is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,

14 **M<sub>i</sub>** is the maximum digital data transfer  
15 load,

16 **C<sub>i</sub>** is the current digital data transfer load,

17 **H** is the file usage factor, and

18 **I** is the file Inter activity factor.

1 64. (Original) The apparatus of claim 61 wherein the second function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 65. (Original) The apparatus of claim 64 wherein the second function to  
2 determine the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4                               where

5                               **Segn** is the a segment size for one segment of the  
6                               remaining segments,

7                               **max** is the maximum function of two variables,

8                               **V** is a total size of the digital data file, and

9                               **f** is determined by the formula:

10                               
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

11                               where

12                               **N<sub>d</sub>** is the number of storage devices  
13                               available to retain the segments of  
14                               the digital data file,

15                               **M<sub>i</sub>** is the maximum digital data transfer  
16                               load,

17                               **C<sub>i</sub>** is the current digital data transfer load,

18                               **H** is the file usage factor, and

19                               **I** is the file Inter activity factor.



1 66. (Original) The apparatus of claim 47 wherein the locations at which the  
2 segments of said data file are located are within the multiple storage devices  
3 of the first computing system.

1 67. (Original) The apparatus of claim 47 wherein the locations at which the  
2 segments of said data file are located are within multiple storage devices of  
3 the plurality of the second computing systems.

1 68. (Original) The apparatus of claim 47 wherein the digital data file is a video file  
2 to be transferred isochronously to at least one of the second computing  
3 systems.

1 69. (Previously Presented) A medium for retaining a computer program to  
2 dynamically segment a digital data file resident within at least one digital data  
3 storage device of multiple digital data storage devices associated with a first  
4 computing system to facilitate transfer of the segmented digital data file from  
5 said first computing system to at least one of a plurality of second computing  
6 systems, whereby said method comprises the steps of

7 a) requesting an identifier for said digital data file;

8 b) requesting a range of locations within the multiple data storage devices  
9 where said digital data file is resident;

10 c) calculating a new segment size list for said digital data file describing a  
11 fragmentation of said digital data file as a function of demand for all digital  
12 data files resident on said digital data storage devices, size of each digital

13 data file of all digital data files, amount of retention space available on  
14 each of the plurality of digital data storage devices, and available  
15 bandwidth for communication with the plurality of second computing  
16 systems;

17 d) if said digital data file has been previously segmented, comparing the new  
18 segment size list to an existing segment size list;

19 e) if the existing segment size list provides a more facilitated transfer of said  
20 digital data file, transferring said digital data file to the second computing  
21 system according to said existing segment size list;

22 f) if the new segment size list provides a more facilitated transfer of said  
23 digital file,

24 creating a new file identifier for each new segment ascertained by the  
25 creating of the new segment size list,

26 creating a new range of locations for each new segment of the digital  
27 data file to identify the location for each new segment, and

28 storing the digital data file at said locations for each new segment;

29 g) transferring each new segment of said digital data file to at least one of  
30 the second computing systems; and

31 repeating steps a) through g) at each request for each digital data file.

1     70.     (Original) The medium of claim 69 wherein calculating the new segment size  
2             list comprises the steps of:

3             determining a number of storage devices attached to said first computing  
4             system available to retain a plurality of segments of said digital data file;

5             determining a maximum digital data transfer load for the storage devices  
6             attached to said first computing system;

7             assigning a minimum segment size which is the smallest amount of digital  
8             data to be contained within one segment of the digital data file;

9             calculating a first segment size as a first function of a number of the storage  
10            devices, the current digital data transfer load, the maximum digital data  
11            transfer load, and the minimum segment size;

12            assigning a last segment size as the minimum segment size;

13            calculating all remaining segment sizes as a second function of the number of  
14            the storage devices, the current digital data transfer load, the maximum  
15            digital data transfer load, and the minimum segment size; and

16            partitioning said digital data file into segments whereby the first segment of  
17            the digital data file is of the first segment size, the last segment of the  
18            digital data file is of the last segment size, and all the remaining segments  
19            of the digital data file is of the remaining segment sized.

71. (Original) The medium of claim 70 wherein the first function to determine the first segment size is:

$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

where

**Seg1** is the first segment size,

**min** is the minimum function of two variables,

**V** is a total size of the digital data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

where

**N<sub>d</sub>** is the number of storage devices  
available to retain the segments of  
the digital data file,

**M<sub>i</sub>** is the maximum digital data transfer  
load, and

**C<sub>i</sub>** is the current digital data transfer load.

72. (Original) The medium of claim 70 wherein the second function to determine the remaining segment sizes is:

$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

where

**Segn** is the a segment size for one segment of the remaining segments,

**max** is the maximum function of two variables,

**V** is a total size of the digital data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

where

**N<sub>d</sub>** is the number of storage devices available to retain the segments of the digital data file,

**M<sub>i</sub>** is the maximum digital data transfer load, and

**C<sub>i</sub>** is the current digital data transfer load.

1     73.     (Original) The medium of claim 70 further comprising the step of:  
2             determining a file interactivity factor describing a number of jumps by the  
3             second computing system within the digital data file.

1     74.     (Original) The medium of claim 73 wherein the first function is further  
2     dependent upon the file interactivity factor.

1     75.     (Original) The medium of claim 74 wherein the first function to determine the  
2     first segment size is:

$$3 \quad \text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5                    **Seg1** is the first segment size,

6 **min** is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

$$9 \quad \mathbf{f} = \mathbf{N}_d + \left( \frac{\mathbf{M}_l}{\mathbf{M}_l} - \mathbf{C}_l \right) + \mathbf{I}$$

10 where

11  $N_d$  is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,  
14  $M_l$  is the maximum digital data transfer  
15 load,  
16  $C_l$  is the current digital data transfer load,  
17 and  
18  $I$  is the file interactivity factor.

1 76. (Original) The medium of claim 73 wherein the second function is further  
2 dependent upon the file interactivity factor.

1 77. (Original) The medium of claim 76 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Segn}$  is the a segment size for one segment of the  
6 remaining segments,

7  $\max$  is the maximum function of two variables,

8  $V$  is a total size of the digital data file, and

9 **f** is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

11 where

12 **N<sub>d</sub>** is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15 **M<sub>i</sub>** is the maximum digital data transfer  
16 load,

17 **C<sub>i</sub>** is the current digital data transfer load,  
18 and

19 **I** is the file Inter activity factor.

1 78. (Original) The medium of claim 70 further comprising the step of:  
2 determining a file usage factor describing a number of requests for said digital  
3 data file for a period of time.

1 79. (Original) The medium of claim 78 wherein the first function is further  
2 dependent upon the file usage factor.

1 80. (Original) The medium of claim 79 wherein the first function to determine the  
2 first segment size is:



3                                    **Seg1 = min(SegSize<sub>min</sub>, V/f)**

4                                    where

5                                    **Seg1** is the first segment size,

6                                    **min** is the minimum function of two variables,

7                                    **V** is a total size of the digital data file, and

8                                    **f** is determined by the formula:

9                                    
$$f = N_d + \left( \frac{M_l}{M_l - C_l} \right) + H$$

10                                   where

11                                   **N<sub>d</sub>** is the number of storage devices  
12                                   available to retain the segments of  
13                                   the digital data file,

14                                   **M<sub>l</sub>** is the maximum digital data transfer  
15                                   load,

16                                   **C<sub>l</sub>** is the current digital data transfer load,  
17                                   and

18                                   **H** is the file usage factor.

1 81. (Original) The medium of claim 79 wherein the second function is further  
2 dependent upon the file usage factor.

1 82. (Original) The medium of claim 81 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Segn** is the a segment size for one segment of the  
6 remaining segments,

7 **max** is the maximum function of two variables,

8 **V** is a total size of the digital data file, and

9 **f** is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

11 where

12 **N<sub>d</sub>** is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15  $M_i$  is the maximum digital data transfer  
16 load,

17  $C_i$  is the current digital data transfer load,  
18 and

19  $H$  is the file usage factor.

1 83. (Original) The medium of claim 70 further comprising the steps of:  
2 determining a file usage factor describing a number of requests for said digital  
3 data file for a period of time; and  
4 determining a file interactivity factor describing a number of jumps by the  
5 second computing system within the digital data file.

1 84. (Original) The medium of claim 83 wherein the first function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 85. (Original) The medium of claim 84 wherein the first function to determine the  
2 first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Seg1}$  is the first segment size,

6  $\min$  is the minimum function of two variables,

7 **V** is a total size of the digital data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

10 where

11 **N<sub>d</sub>** is the number of storage devices  
12 available to retain the segments of  
13 the digital data file,

14 **M<sub>i</sub>** is the maximum digital data transfer  
15 load,

16 **C<sub>i</sub>** is the current digital data transfer load,

17 **H** is the file usage factor, and

18 **I** is the file Inter activity factor.

1 86. (Original) The medium of claim 83 wherein the second function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 87. (Original) The medium of claim 86 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4                               where

5                               **Segn** is the a segment size for one segment of the  
6                               remaining segments,

7                               **max** is the maximum function of two variables,

8                               **V** is a total size of the digital data file, and

9                               **f** is determined by the formula:

10                               
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

11                               where

12                               **N<sub>d</sub>** is the number of storage devices  
13                               available to retain the segments of  
14                               the digital data file,

15                               **M<sub>i</sub>** is the maximum digital data transfer  
16                               load,

17                               **C<sub>i</sub>** is the current digital data transfer load,

18                               **H** is the file usage factor, and

19                               **I** is the file Inter activity factor.

1 88. (Original) The medium of claim 69 wherein the locations at which the  
2 segments of said data file are located are within the multiple storage devices  
3 of the first computing system.

1 89. (Original) The medium of claim 69 wherein the locations at which the  
2 segments of said data file are located are within multiple storage devices of  
3 the plurality of the second computing systems.

1 90. (Original) The medium of claim 69 wherein the digital data file is a video file to  
2 be transferred isochronously to at least one of the second computing  
3 systems.

1 91. (Currently Amended) A digital video data service system in communication  
2 with a plurality of computing systems to provide at least one digital video data  
3 file of a plurality of digital video data files to at least one of the plurality of  
4 computing systems, comprising:

5 a plurality of digital video data file storage devices in communication  
6 with each other and with any of the plurality of computing systems  
7 for storing a plurality of dynamically generated segments of said  
8 provided digital video data file, said segments stored within said  
9 plurality of digital video data file storage devices to facilitate  
10 transfer of said provided digital video data file to at least one of the  
11 plurality of computing systems; and

12 a segmentation apparatus in communication with the plurality of digital  
13 video data file storage devices, which, at a request of any of the  
14 digital video data files, dynamically fragments any requested digital  
15 video data file into a plurality of segments to facilitate transfer to  
16 and processing by at least one of the second computing systems  
17 of said segments, ~~wherein if said requested digital video data file~~  
18 ~~has been previously segmented, a new segment size list is~~  
19 ~~compared to an existing segment size list, wherein the~~  
20 segmentation apparatus performs the steps of:

- 21 a) requesting an identifier for said digital video data file;
- 22 b) requesting a range of locations within the multiple data  
23 storage devices where said digital video data file is resident;
- 24 c) calculating the new segment size list for said digital video  
25 data file describing a fragmentation of said digital video data  
26 file as a function of demand for all digital video data files  
27 resident on said digital video data storage devices, size of  
28 each digital video data file of all digital video data files,  
29 amount of retention space available on each of the plurality  
30 of digital video data storage devices, and available  
31 bandwidth for communication with the plurality of computing  
32 systems;

- 33                    d) if said digital data file has been previously segmented,  
34                    comparing the new segment size list to an existing segment  
35                    size list;
- 36                    e) if the existing segment size list provides a more facilitated  
37                    transfer of said digital data file, transferring said digital data  
38                    file to the computing system according to said existing  
39                    segment size list;
- 40                    f) if the new segment size list provides a more facilitated  
41                    transfer of said digital file,
- 42                    creating a new file identifier for each new segment  
43                    ascertained by the creating of the new segment size  
44                    list,
- 45                    creating a new range of locations for each new segment  
46                    of the digital data file to identify the location for each  
47                    new segment, and
- 48                    storing the digital data file at said locations for each new  
49                    segment;
- 50                    g) transferring each new segment of said digital data file to at  
51                    least one of the computing systems; and



52                                    h) repeating steps a) through g) at each request for each  
53                                    digital data file.

1     92.     (Cancelled)

1     93.     (Currently Amended) The system of ~~claim 92~~ claim 91 wherein calculating the  
2             new segment size list comprises the steps of:

3             determining a number of storage devices attached to said first computing  
4             system available to retain a plurality of segments of said digital video data  
5             file;

6             determining a maximum digital video data transfer load for the storage  
7             devices attached to said first computing system;

8             assigning a minimum segment size which is the smallest amount of digital  
9             video data to be contained within one segment of the digital video data  
10            file;

11            calculating a first segment size as a first function of a number of the storage  
12            devices, the current digital video data transfer load, the maximum digital  
13            video data transfer load, and the minimum segment size;

14            assigning a last segment size as the minimum segment size;

15            calculating all remaining segment sizes as a second function of the number of  
16            the storage devices, the current digital video data transfer load, the

17 maximum digital video data transfer load, and the minimum segment size;  
18 and

19 partitioning said digital video data file into segments whereby the first  
20 segment of the digital video data file is of the first segment size, the last  
21 segment of the digital video data file is of the last segment size, and all  
22 the remaining segments of the digital video data file is of the remaining  
23 segment sized.

1 94. (Original) The system of claim 93 wherein the segmentation apparatus the  
2 further performs the steps of:

3 assigning one of the number of storage devices to retain each segment of the  
4 digital video data file; and

5 assigning an address within the storage devices to identify the location of an  
6 assigned segment.

1 95. (Original) The system of claim 93 wherein the first function to determine the  
2 first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Seg1** is the first segment size,

6 **min** is the minimum function of two variables,

7 **V** is a total size of the digital video data file, and

8 **f** is determined by the formula:

9 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

10 where

11 **N<sub>d</sub>** is the number of storage devices  
12 available to retain the segments of  
13 the digital video data file,

14 **M<sub>i</sub>** is the maximum digital video data  
15 transfer load, and

16 **C<sub>i</sub>** is the current digital video data transfer  
17 load.

1 96. (Original) The system of claim 93 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Segn** is the a segment size for one segment of the  
6 remaining segments,

7                    **max** is the maximum function of two variables,

8                    **V** is a total size of the digital video data file, and

9                    **f** is determined by the formula:

10                    
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right)$$

11                    where

12                    **N<sub>d</sub>** is the number of storage devices  
13                    available to retain the segments of  
14                    the digital video data file,

15                    **M<sub>i</sub>** is the maximum digital video data  
16                    transfer load, and

17                    **C<sub>i</sub>** is the current digital video data transfer  
18                    load.

1    97.    (Original) The system of claim 93 further comprising the step of:  
  
2            determining a file interactivity factor describing a number of jumps by the  
3            computing system within the digital video data file.

1    98.    (Original) The system of claim 97 wherein the first function is further  
2            dependent upon the file interactivity factor.

1     99.     (Original) The system of claim 98 wherein the first function to determine the  
2             first segment size is:

3                             **Seg1 = min(SegSize<sub>min</sub>, V/f)**

4                             where

5                             **Seg1** is the first segment size,

6                             **min** is the minimum function of two variables,

7                             **V** is a total size of the digital video data file, and

8                             **f** is determined by the formula:

9     
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

10                             where

11     **N<sub>d</sub>** is the number of storage devices  
12     available to retain the segments of  
13     the digital video data file,

14     **M<sub>i</sub>** is the maximum digital video data  
15     transfer load,

16     **C<sub>i</sub>** is the current digital video data transfer  
17     load, and

18 I is the file interactivity factor.

1 100. (Original) The system of claim 97 wherein the second function is further  
2 dependent upon the file interactivity factor.

1 101. (Original) The system of claim 100 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5 **Segn** is the a segment size for one segment of the  
6 remaining segments,

7 **max** is the maximum function of two variables,

8 **V** is a total size of the digital video data file, and

9 **f** is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + I$$

11 where

12 **N<sub>d</sub>** is the number of storage devices  
13 available to retain the segments of  
14 the digital video data file,

15  $M_i$  is the maximum digital video data  
16 transfer load,

17  $C_i$  is the current digital video data transfer  
18 load, and

19  $I$  is the file Inter activity factor.

1 102. (Original) The system of claim 93 further comprising the step of:  
2 determining a file usage factor describing a number of requests for said digital  
3 video data file for a period of time.

1 103. (Original) The system of claim 102 wherein the first function is further  
2 dependent upon the file usage factor.

1 104. (Original) The system of claim 103 wherein the first function to determine the  
2 first segment size is:

3 
$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Seg1}$  is the first segment size,

6  $\min$  is the minimum function of two variables,

7  $V$  is a total size of the digital video data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

where

**N<sub>d</sub>** is the number of storage devices  
available to retain the segments of  
the digital video data file,

**M<sub>i</sub>** is the maximum digital video data  
transfer load,

**C<sub>i</sub>** is the current digital video data transfer  
load, and

**H** is the file usage factor.

105. (Original) The system of claim 102 wherein the second function is further  
dependent upon the file usage factor.

106. (Previously Presented) The system of claim 105 wherein the second function  
to determine the remaining segment sizes is:

$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

where



**Segn** is the a segment size for one segment of the  
remaining segments,

**max** is the maximum function of two variables,

**V** is a total size of the digital video data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H$$

where

**N<sub>d</sub>** is the number of storage devices  
available to retain the segments of  
the digital video data file,

**M<sub>i</sub>** is the maximum digital video data  
transfer load,

**C<sub>i</sub>** is the current digital video data transfer  
load, and

**H** is the file usage factor.

107. (Original) The system of claim 93 further comprising the steps of:

determining a file usage factor describing a number of requests for said digital video data file for a period of time; and

determining a file interactivity factor describing a number of jumps by the computing system within the digital video data file.

108. (Original) The system of claim 107 wherein the first function is further dependent upon the file usage factor and the file interactivity factor.

109. (Original) The system of claim 108 wherein the first function to determine the first segment size is:

$$\text{Seg1} = \min(\text{SegSize}_{\min}, V/f)$$

where

**Seg1** is the first segment size,

**min** is the minimum function of two variables,

**V** is a total size of the digital video data file, and

**f** is determined by the formula:

$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

where

11  $N_d$  is the number of storage devices  
12 available to retain the segments of  
13 the digital video data file,  
14  $M_i$  is the maximum digital video data  
15 transfer load,  
16  $C_i$  is the current digital video data transfer  
17 load,  
18  $H$  is the file usage factor, and  
19  $I$  is the file Inter activity factor.

1 110. (Original) The system of claim 107 wherein the second function is further  
2 dependent upon the file usage factor and the file interactivity factor.

1 111. (Original) The system of claim 110 wherein the second function to determine  
2 the remaining segment sizes is:

3 
$$\text{Segn} = \max(\text{SegSize}_{\min}, V/f)$$

4 where

5  $\text{Segn}$  is the a segment size for one segment of the  
6 remaining segments,

7  $\max$  is the maximum function of two variables,

8 V is a total size of the digital video data file, and

9 f is determined by the formula:

10 
$$f = N_d + \left( \frac{M_i}{M_i - C_i} \right) + H + I$$

11 where

12  $N_d$  is the number of storage devices  
13 available to retain the segments of  
14 the digital data file,

15  $M_i$  is the maximum digital data transfer  
16 load,

17  $C_i$  is the current digital data transfer load,

18  $H$  is the file usage factor, and

19  $I$  is the file Inter activity factor.

1 112. (Original) The system of claim 93 wherein the locations at which the  
2 segments of said data file are located are within the multiple storage devices  
3 of the first computing system.

1 113. (Original) The system of claim 93 wherein the locations at which the  
2 segments of said data file are located are within multiple storage devices of  
3 the plurality of the computing systems.

- 1    114.    (Original) The system of claim 91 wherein the digital video data file is  
2           transferred isochronously to the computing system.